

MOLD TEMPERATURE CONTROLLER (WATER & OIL)

FEATURE :

- PID controller with deviation within $+0.1^{\circ}\text{C}$.
- There are 6 protective devices: auto-exhaust by start-up and auto-cooling by turn-off, Anti-phases, short of phases, water pump protection, overheat and short of oil level.
- LCD screen shows the setting and actual temperature of machine.
- Easy for operations and maintenance.
- Stainless steel water tank is durable and keep from the trouble of leakage and rust.
- With recycling oil run-way.
- Exquisite appearance with small footprint.



YT-TM9KW-0

SPECIFICATIONS

Model	Transfer Medium	Max. Temp.	Pump (KW)	Pump Flow (L/min)	Loading Distance (m)	Heating Power(KW)	Inlet/Outlet Diameter	Dimension(mm)	Approx.Net Weight (KG)
YT-TM6KW-W	Water	100°C	0.37	42	28	6	3/8" x 2	730*310*643	45
YT-TM9KW-W			0.75	56	28	9	3/8" x 4	730*310*643	46
YT-TM12KW-W			0.75	56	38	12	3/8" x 4	730*310*643	50
YT-TM18KW-W			1.5	160	27	9*2	1" x 1	830*370*694	65
YT-TM24KW-W			1.5	160	27	12*2	1" x 1	990*520*983	100
YT-TM36KW-W			2.2	315	26	12*3	1.5" x 1	1090*520*983	110
YT-TM6KW-O	Heat Transfer Oil	200°C	0.37	33	22	6	3/8" x 2	730*310*643	52
YT-TM9KW-O			0.75	45	30	9	3/8" x 4	730*310*643	55
YT-TM12KW-O			0.75	45	30	12	3/8" x 4	730*310*643	55
YT-TM18KW-O			1.5	128	21	9*2	1" x 1	830*370*694	68
YT-TM24KW-O			1.5	128	21	12*2	1" x 1	990*520*983	110
YT-TM36KW-O			2.2	252	21	12*3	1.5" x 1	1090*520*983	113

Note: We reserve the right to cancel or change the above specific model without any prior notice.