

FEATURE :

- Flake cutter blades are suitable for recycling and restoring of conventional sheets, tube plastics, profiles, packing plastics, extrusion mold products and runners, etc.
- YT-GP series granulators are adopted with sealed bearings which can handle long hour operation. The unique design of the cutter ensures the equality of granule sizes. The cutters are treated thermal processing.
- Within 400 models installed casters. Above 500 models installed anti vibration mounts as optional.

**YT-GP400**

Standard application



Cutter saddle, cutter

Screen mesh
Customized screen mesh
available

Flake cutter saddle

Note: We reserve the right to cancel or change the above specific model without any prior notice.

PLASTIC CRUSHER - FLAKE TYPE

DTS

SPECIFICATIONS

Model	YT-GP230	YT-GP300	YT-GP400	YT-GP500	YT-GP600	YT-GP800	YT-GP960	YT-GP1100	YT-GP1200
Grinding Chamber(mm)	230x200	310x200	410x240	510x300	610x330	815x470	960x610	1100x800	1200x800
Grinding Capacity(KG/H)	100-150	150-200	200-250	300-350	350-450	450-600	800-1000	1000-1200	1000-1500
Stationary Cutter	2	2	2	2	4	4	4	4	4
Rotary Cutter	6	9	12	15	19	24	30	33	36
Mesh size(mm)	φ8	φ8	φ8	φ10	φ10	φ10	φ12	φ12	φ12
Power	KW	4	5.5	7.5	11	15	22/30	37/45/57	75
	HP	5	7.5	10	15	20	30/40	50/60/75	100
Dimensions(LxWxH mm)	890x640x1145	1010x715x1300	1010x815x1330	1290x975x1670	1290x1075x1740	1735x1525x2180	1950x1780x2740	2510x2080x3700	2510x2100x3700
Approx. Net Weight(KG)	280	435	500	900	970	2000	3000	6000	6500
Dimension for SP(mm)	1200x870x1510	1320x840x1580	1320x940x1680	1640x1080x1980	1940x1180x2050	1850x1540x2680	2050x1850x2860	2590x2230x3610	2590x2230x3610
Collective Blower(KW)	1.5	1.5	1.5	2.2	2.2	3	4	7.5	7.5
Approx. N.W. for SP(KG)	400	435	604	900	1180	2380	3500	6500	6800

SP stands for soundproof granulator with collecting device.

Note: We reserve the right to cancel or change the above specific model without any prior notice.